



SECURITY LIGHTING

Model No. OS-1-TS Twin Spot Sensor
Model No. OS-1-SS Single Spot Sensor
Model No. OS-110 Stand Alone Sensor 110°

FEATURES

- Manual Override
- Adjustable Time, Distance and Lux
- For Incandescent, Halogen and Fluorescent Lights
- Easy Installation; Pre-wired (except OS-110)
- Wall or Ceiling Mount
- Stainless Steel Screws
- Available in Black, White, Silver or Beige (OS110 only)
- Lamps not included

TECHNICAL SPECIFICATIONS


- Power: 240V AC 50Hz
- 1000W (Max) Lighting Load for Incandescent Lights
- 500W (Max) for Halogen Lights
- 250W (Max) for Fluorescent Lights
- Environmental Protection to IP44
- 6 Seconds to 12 Minutes Adjustable Shut Off Time
- 110° Elliptical View Field, 9 Metres on each Side, 12 Metres Forward



OS-1-TS - Twin Spot Sensor
Black (Model No. 55-023)
White (Model No. 55-021)



OS-1-SS - Single Spot Sensor
Black (Model No. 55-223)
White (Model No. 55-221)




OS-110 - Sensor 110°
Black (Model No. 55-101)
White (Model No. 55-110)
Silver (Model No. 55-102)
Beige (Model No. 55-103)



OS-230 Stand Alone Sensor 200°

OS-230 - Sensor 200°
White (Model No. 55-036)



FEATURES

- Large Area of Detection; 200°
- For Incandescent, Halogen and Fluorescent Lights
- Manual Override
- Adjustable Time, Distance and Lux
- Wall or Ceiling Mount
- Stainless Steel Screws
- Available in White only

TECHNICAL SPECIFICATIONS

- Power: 240V AC 50Hz
- 1000W (Max) Lighting load for Incandescent Lights
- 500W (Max) for Halogen Lights
- 250W (Max) for Fluorescent Lights
- Environmental Protection to IP44
- 6 Seconds to 12 Minutes adjustable shut off time
- 200° Detection Range, 12 Metres Forward



Single PVC Lampholder Pack

Black (Model No. 55-015)

White (Model No. 55-016)
(Lamp NOT INCLUDED)

- 1x Universal Base Plate
- 1x Junction Box
- 1x PAR38 Lamp Holder
- 1x Gasket
- 1x Connector/Stainless Steel Screw Pack



Twin PVC Lampholder Pack

Black (Model No. 55-013)

White (Model No. 55-014)
(Lamps NOT INCLUDED)

- 1x Base Plate
- 1x Junction Box
- 2x PAR38 Lamp Holders
- 1x Gasket
- 1x Connector/Stainless Steel Screw Pack





SECURITY LIGHTING

OS-2-TH Twin Halogen Sensor OS-2-SH Single Halogen Sensor

FEATURES

- 2 X 100W G9 Tungsten Halogen Lamps (OS-2-TH)
- Aluminium Casting Lamp Holders
- Manual Override Facility
- Adjustable Time, Distance and Lux
- Wall or Ceiling Mount
- Easy Installation; Pre-wired
- Stainless Steel Screws
- Available in Black, White, Silver and Beige

TECHNICAL SPECIFICATIONS

- Power: 240V AC 50Hz
- 200W (Max) for Halogen Lights
- Environmental Protection to IP44
- 6 Seconds to 12 Minutes Adjustable Shut Off Time
- 110° Elliptical View Field, 9 Metres on each Side, 12 Metres Forward
- Certificate of Approval #Q03112



OS-2-TH - Twin Halogen Sensor

(Includes 2x 100W Lamps)

White (Model No. 55-121)

Black (Model No. 55-123)

Silver (Model No. 55-129)

Beige (Model No. 55-130)



OS-2-SH Single Halogen Sensor


(Includes 1x 100W Lamp)

White (Model No. 55-122)

Black (Model No. 55-124)

Silver (Model No. 55-131)

Beige (Model No. 55-132)



Single Halogen Lamp Pack

Black (Model No. 55-115)

White (Model No. 55-116)

Silver (Model No. 55-119)

Beige (Model No. 55-134)

- 1x 100W G9 Tungsten Halogen Lamp
- 1x Aluminium Casting Lamp Holder
- 1x Universal Base Plate
- 1x Junction Box
- 1x Gasket
- 1x Connector/Stainless Steel Screw Pack



Twin Halogen Lamp Pack

Black (Model No. 55-113)

White (Model No. 55-114)

Silver (Model No. 55-120)

Beige (Model No. 55-133)

- 2x 100W G9 Tungsten Halogen Lamps
- 2x Aluminium Casting Lamp Holders
- 1x Aluminium Base Plate
- 1x Junction Box
- 1x Gasket
- 1x Connector/Stainless Steel Screw Pack



Tungsten Halogen Lamps 240V (G9)

AVAILABLE IN

100W (Model No. 55-200)

75W (Model No. 55-201)

60W (Model No. 55-202)

40W (Model No. 55-203)

25W (Model No. 55-204)



Glass for Aluminium Lamp Holders (per pair)

Red (Model No. 55-125)

Yellow (Model No. 55-126)

Green (Model No. 55-127)

Blue (Model No. 55-128)

