

DOOR BEAM OUTDOOR



45-150



45-200



Description	Colour	Model
Photoelectric Beam & Reflector, IP66, 12m, IR1200L	Black	45-150
Photoelectric Beam Sensor, IP66, 30m, IR3000L	Black	45-200

- Universal AC/DC input voltage
- Suitable for warehouse, drive through bottle shop, industrial automation, entry passing detection, gate or garage door

TECHNICAL DATA

Detection Type	Retro Reflection (45-150) or Through Beam (45-200)
Sensing Range	12m (45-150) or 30m (45-200)
Output Method	Normally Closed Relay
Input Voltage	45-150 Both AC/DC 12-240V Free Power 45-200 DC 12-240V +/- 10% or AC 24-240V +/- 10%
Response Time	15Ms
Emitting Element	IR LED
Power LED Indicator Green	When Powered; LED Turn On When Power Off; LED Turn Off
Current Consumption	Beam Aligned: 52mA, Broken 32mA
Environmental Protection	IP66
Operating Temperature	-20 °C to -55 °C

ACCESSORIES

Description	Model
12V DC 1000mA Power Supply for 45-150 and 45-200	01-121
12V DC Buzzer with Cable, 90dB, 12VDC, 22mm Diameter, 12mm High	70-415
Universal Timer Board (For Setting Amount of Time Buzzer Sounds)	26-001
Hood for 45-150 Reflector	45-106



01-121



70-415



26-001