

**MINI FLUSH PRESCENCE DETECTOR, 360 DEGREES**



**55-368PAi**

Description	Colour	Model
Mini Flush Mount Presence Detector	White	55-368PAi

- Manual override
- Adjustable time, distance & Lux
- Integrated power box
- Cutout diameter 38mm
- 300mm pre-wired cable
- Polycarbonate construction
- Minimum load 10W

**TECHNICAL DATA**

<b>Mounting</b>	Wall/Ceiling
<b>Sensor Type</b>	Passive IR
<b>Detection Range</b>	6m Diameter at a 2.5m Mounting Height
<b>Detection Angle</b>	360° Adjustable with Lens Shield
<b>Time on Adjustment</b>	From 5 seconds to 30 minutes
<b>Lux Setting (Lux)</b>	5 to 2000
<b>Load</b>	- 400W (Max) for LED Lamp - 1000W (Max) for Halogen Lamp - 1000VA/600W (Max) for Low Voltage Halogen Lamp - 600VA/400W (Max) Energy Saving lamp - 1000VA/600W (Max) Fluorescent lamp - 2000W (Max) Incandescent lamp
<b>Voltage</b>	240V AC 50Hz
<b>Operating Temperature</b>	-10°C to +50°C
<b>Environmental Protection</b>	IP55/Class II
<b>Cutout</b>	ø 38mm

