## **STAND ALONE SENSOR 180 DEGREES**










55-188

Description	Colour	Model
Stand Alone Sensor 180 Degrees	White	55-188
<ul> <li>Adjustable time, distance &amp; Lux</li> <li>Large terminal block</li> <li>Energy efficient, less than 0.5W in standby mode</li> </ul>	<ul> <li>Stainless steel screws</li> <li>Suitable for HVAC applications</li> <li>Polycarbonate construction</li> <li>Minimum load 10W</li> </ul>	



73.5mm

## **TECHNICAL DATA**

Mounting	Wall/Ceiling
Sensor Type	Passive IR
<b>Detection Range</b>	12m at a 2m Mounting Height
Detection Angle	180° Rotatable 90° Left to Right
Time on Adjustment	From 5 seconds to 30 minutes
Lux Setting (Lux)	10 to 2000
Load	- 150W (Max) for LED Lamp
	- 500W (Max) for Halogen Lamp
	- 300VA (Max for Low Voltage Halogen Lamp
	- 250VA/ 150W (Max) Energy Saving lamp
	- 300VA/ 100W (Max) Fluorescent lamp
	- 250VA/ 1000W (Max) Incandescent lamp
Voltage	240V AC 50Hz
Operating Temperature	-20°C to +50°C
Environmental Protection	IP65

