

### DOOR BEAM OUTDOOR



45-150



45-200



Description	Colour	Model
Photoelectric Beam & Reflector, IP66, 12m, IR1200L	Black	45-150
Photoelectric Beam Sensor, IP66, 30m, IR3000L	Black	45-200

- Universal AC/DC input voltage
- Suitable for warehouse, drive through bottle shop, industrial automation, entry passing detection, gate or garage door

### TECHNICAL DATA

<b>Detection Type</b>	Retro Reflection (45-150) or Through Beam (45-200)	
<b>Sensing Range</b>	12m (45-150) or 30m (45-200)	
<b>Output Method</b>	Normally Closed Relay	
<b>Input Voltage</b>	45-150	Both AC/DC 12-240V Free Power
	45-200	DC 12-240V +/- 10% or AC 24-240V +/- 10%
<b>Response Time</b>	15Ms	
<b>Emitting Element</b>	IR LED	
<b>Power LED Indicator Green</b>	When Powered; LED Turn On When Power Off; LED Turn Off	
<b>Current Consumption</b>	Beam Aligned: 52mA, Broken 32mA	
<b>Environmental Protection</b>	IP66	
<b>Operating Temperature</b>	-20°C to -55°C	

### ACCESSORIES

Description	Model
12V DC 1000mA Power Supply for 45-150 and 45-200	01-121
12V DC Buzzer with Cable, 90dB, 12VDC, 22mm Diameter, 12mm High	70-415
Universal Timer Board (For Setting Amount of Time Buzzer Sounds)	26-001
Hood for 45-150 Reflector	45-106



01-121



70-415



26-001